

MS8044 1/2"(3/4") MALE XCEL WOBBLER SPRINKLER

Specification:

Connection Size: 1/2" or 3/4" male

Working Pressure: 0.69-1.72bar

Wet Diameter: 9.8-16.9m

Flow Rate: 177-1788L/H



Features and Applications:

- Available in High Angle and Middle Angle
- Multiple Choice for color-coded nozzle
- EXCLUSIVE NYLON material
- 9 outlets and 12 outlets model available

Nozzle		Pressure Bar	Flow L/H	Diameter	
#	Size			High Angle(M)	Mid Angle(M)
6	2.38mm	0.69	177	11.1	9.8
		1.03	216	12.5	10.7
		1.38	250	13.7	11.7
		1.72	279	14.0	12.5
7	2.78mm	0.69	241	12.2	10.1
		1.03	295	14.2	11.1
		1.38	341	14.3	12.4
		1.72	382	15.4	12.5
8	3.18mm	0.69	318	12.8	10.4
		1.03	388	14.2	11.7
		1.38	480	14.3	12.5
		1.72	502	15.7	13.0
9	3.57mm	0.69	409	13.4	10.5
		1.03	500	14.3	12.4
		1.38	577	15.4	12.8
		1.72	645	16.0	13.1
10	3.97mm	0.69	504	13.6	11.0
		1.03	618	14.9	12.5
		1.38	713	15.4	13.0
		1.72	797	16.3	13.4
11	4.37mm	0.69	611	13.6	11.1
		1.03	749	15.4	12.7
		1.38	865	15.7	13.1
		1.72	968	16.5	13.4
12	4.76mm	0.69	734	14.0	11.1
		1.03	899	15.4	12.7
		1.38	1038	15.9	13.6
		1.72	1161	16.6	13.6
13	5.16mm	0.69	863	14.2	11.1
		1.03	1056	15.6	12.7
		1.38	1222	16.0	13.6
		1.72	1365	16.9	13.7
14	5.56mm	0.69	999	14.3	11.3
		1.03	1224	15.6	13.0
		1.38	1415	16.2	13.7
		1.72	1583	16.9	14.2
15	5.95mm	0.69	1010	14.4	11.4
		1.03	1450	15.8	13.2
		1.38	1650	16.3	13.8
		1.72	1788	16.9	14.2