

# MS8045 1/2" MALE MINI WOBBLER SPRINKLER

## Specification:

Connection Size: 1/2" male

Working Pressure: 1.03-1.72bar

Wet Diameter: 9.5-15.9m

Flow Rate: 95-797L/H

## Features and Applications:

- Available in High Angle and Standard Angle
- Multiple Choice for color-coded nozzle
- EXCLUSIVE POM material, ensure smooth rotary



Nozzle		Pressure Bar	Flow L/H	Diameter	
#	Size			High Angle(M)	Std Angle(M)
4	1.59mm	1.03	95	13.7	9.5
		1.38	114	14.1	9.8
		1.72	127	14.4	10.1
5	1.98mm	1.03	145	13.9	11.1
		1.38	170	14.3	11.9
		1.72	191	14.6	12.0
6	2.38mm	1.03	216	14.2	12.0
		1.38	250	14.5	12.8
		1.72	284	14.9	12.8
7	2.78mm	1.03	295	14.5	12.5
		1.38	343	14.8	13.1
		1.72	384	15.1	13.1
8	3.18mm	1.03	379	14.7	12.7
		1.38	443	15.1	13.1
		1.72	495	15.4	13.3
9	3.57mm	1.03	500	15.0	12.9
		1.38	577	15.3	13.2
		1.72	645	15.6	13.5
10	3.97mm	1.03	618	15.3	13.0
		1.38	713	15.6	13.3
		1.72	797	15.9	13.6

