



**RIEGO  
ECUADOR**



AS0180B / AS0180H						
Click	Working Preaure (Bar) VS Discharge(L/h)					
	0.5Bar	1.0Bar	1.5Bar	2.0Bar	2.5Bar	3.0Bar
2	5	7	10	13	15	17
4	14	22	25	30	39	41
8	22	38	50	59	71	77
12	31	48	63	74	84	91
16	38	58	71	84	94	126
20	41	63	77	90	103	112
24	42	65	85	99	110	125
30	51	75	93	106	122	134
32	50	81	93	106	122	133
Sprayer Diameter		0.1–2.2m / 0.1–2.8m				

## Advantages:

**Uniform Coverage:** The full-circle sprayer delivers fine water droplets for even distribution, enhancing both irrigation and landscape aesthetics.

**Customizable Range:** The adjustable spraying radius allows for precise control over water coverage by simply turning the sprayer's cover.

**Maintenance Friendly:** The easy-removal cover facilitates quick inspection and thorough cleaning of the dripper, ensuring optimal performance.

**Seamless Integration:** The AS0180B model offers hassle-free installation, fitting directly onto Dn12-32mm PE pipes with a barb offtake.

**Versatile Attachment:** The AS0180H model is designed for convenient connection to Dn5/3mm PVC or Dn6mm PE tubing, with a spike for easy planting proximity.

**Durable Construction:** Crafted from high-quality raw plastic material, the product is built to be anti-corrosive, UV-resistant, and long-lasting against aging

24 de Septiembre SN y Pedro Vallejo, Tababela, Quito

Telf: 099 441 4588 / 098 716 4387

E-mail: [ventas@riegoecuador.com](mailto:ventas@riegoecuador.com)

[www.riegoecuador.com](http://www.riegoecuador.com)